


GRUPOS DE COMPRESSOR SCROLL COPELAND R404A

MODELO	Frequencia	GAS	Temp. evap. -10°	Temp. evap. -25°	Temper. de condensação
LT-ZB15-2	380/50HZ	R404A	3700W	1870W	-40°
LT-ZB19-2.5	380/50HZ	R404A	4550W	2490W	-40°
LT-ZB21-3	380/50HZ	R404A	5500W	3000W	-40°
LT-ZB26-3.5	380/50HZ	R404A	6350W	3500W	-40°
LT-ZB29-4	380/50HZ	R404A	7500W	4050W	-40°
LT-ZB38-5	380/50HZ	R404A	9300W	5100W	-40°
LT-ZB46-6	380/50HZ	R404A	10950W	6000W	-40°
LT-ZB58-8	380/50HZ	R404A	14400W	7050W	-40°
LT-ZB76-10	380/50HZ	R404A	19400W	10900W	-40°

GRUPOS INSONORIZADOS DE COMPRESSOR SCROLL COPELAND R404A

MODELO	Voltagem / Frequencia	GAS	Temp. evap. -10°	Temp. evap. -25°	Temper. de condensação
LTW02LAY	380/50HZ	R404A	3700W	1870W	-40°
LTW03LAY	380/50HZ	R404A	5500W	3000W	-40°
LTW04LAY	380/50HZ	R404A	7500W	4050W	-40°
LTW05LAY	380/50HZ	R404A	9300W	5100W	-40°
LTW06LAY	380/50HZ	R404A	10950W	6000W	-40°
LTW09LAY	380/50HZ	R404A	16400W	8900W	-40°

GRUPOS DE COMPRESSOR BOYARD R404A

MODELO	Potência	Volt./Freq.	GAS	Capacidade (w) a diferentes temp. de evaporação					
				-40°	-30°	-23.3°	-20°	-15°	-10°
HQXD-13K	0,75HP	220/50HZ	R404A	430	700	845	995	1230	1506
HQXD-16K	1HP	220/50HZ	R404A	539	880	1046	1235	1515	1840
HQXD-23K	1,5HP	220/50HZ	R404A	785	1280	1516	1790	2185	2645
HQXD-30K	2HP	220/50HZ	R404A	1023	1667	1951	2320	2832	3430
HQXD-36K	2,5HP	220/50HZ	R404A	1200	1955	2303	2720	3315	4020
CDLX-065K	0,75HP	220/50HZ	R404A	430	700	845	995	1230	1506
CDLX-085K	1HP	220/50HZ	R404A	539	880	1046	1235	1515	1840
CDLX-123K	1,5HP	220/50HZ	R404A	785	1280	1516	1790	2185	2645
CDLX-158K	2HP	220/50HZ	R404A	1023	1667	1951	2320	2832	3430
CDLX-180K	2,5HP	220/50HZ	R404A	1200	1955	2303	2720	3315	4020